

# 产品编码规则



## 附加功能

- 00: 常规
- 01: 阻抗保护、反接保护、缓启动
- 02: FG功能
- 03: RD功能
- 04: PWM调速功能
- 05: FG+PWM功能
- 06: RD+PWM功能
- 07: TC温控调速功能
- 08: CS恒速功能
- 09: 正反转功能

※ 编号不代表所示功能，一切以客户确认为准。

## 产品材质

P: 塑胶型 M: 金属型 T: 增压型

## 产品类型

A: 轴流风机 B: 涡轮风机

## 产品转速

L: 低转速 M: 中转速  
H: 高转速 U: 超高转速

## 额定电压

1: 3~5V 2: 9~12V 3: 18V  
4: 24V 5: 36V 6: 48V  
7: 110V 8: 220V 9: 380V

## 轴承结构

B: 滚珠轴承 S: 含油/液压轴承

## 产品尺寸

### 轴流风扇系列

- |                  |                    |
|------------------|--------------------|
| 2507: 25x25x7mm  | 6020: 60x60x20mm   |
| 2510: 25x25x10mm | 6025: 60x60x25mm   |
| 3006: 30x30x6mm  | 6038: 60x60x38mm   |
| 3007: 30x30x7mm  | 7015: 70x70x15mm   |
| 3010: 30x30x10mm | 7020: 70x70x20mm   |
| 3510: 35x35x10mm | 7025: 70x70x25mm   |
| 4007: 40x40x7mm  | 8010: 80x80x10mm   |
| 4010: 40x40x10mm | 8015: 80x80x15mm   |
| 4015: 40x40x15mm | 8020: 80x80x20mm   |
| 4020: 40x40x20mm | 8025: 80x80x25mm   |
| 4028: 40x40x28mm | 8038: 80x80x38mm   |
| 4510: 45x45x10mm | 9225: 92x92x25mm   |
| 5010: 50x50x10mm | 9238: 92x92x38mm   |
| 5015: 50x50x15mm | 1225: 120x120x25mm |
| 5020: 50x50x20mm | 1238: 120x120x38mm |
| 6010: 60x60x10mm | 1751: 170x152x51mm |
| 6015: 60x60x15mm |                    |

### 涡轮风扇系列

- 3007: 30x30x7mm
- 4010: 40x40x10mm
- 4510: 45x45x10mm
- 5010: 50x50x10mm
- 5015: 50x50x15mm
- 5020: 50x50x20mm
- 5025: 50x50x25mm
- 6015: 60x60x15mm
- 6025: 60x60x25mm
- 7515: 75x75x15mm
- 7525: 75x75x25mm
- 7530: 75x75x30mm
- 9020: 90x90x20mm
- 9733: 97x97x33mm
- 1232: 120x120x32mm

### 交流风扇系列

- 8025: 80x80x25mm
- 9225: 92x92x25mm
- 1225: 120x120x25mm
- 1238: 120x120x38mm
- 1550: 150x150x50mm
- 1751: 170x152x51mm
- 1860: 180x180x60mm
- 2060: 200x200x60mm
- 2260: φ220x60mm
- 2589: φ254x89mm

## 电流类别

D: 直流系列 A: 交流系列

## 风之源品牌风机



※ 风之源产品型号会不定期添加更新，此表格仅供参考，及时参数请登录官网查询。